



SERIES ST

MULTILEVEL MIXED OVENS

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47 Казахстан (772)734-952-31 Таджикистан (992)427-82-92-69

<http://fmind.nt-rt.ru> || fdm@nt-rt.ru

ST 604

REF. 710316



4 x 600 x 400

4 x GN 1/1

ST 604 GAS

REF. 710318



4 x 600 x 400

4 x GN 1/1

EQUIPMENT

- Cycle end alarm
- Door safety switch
- Safety thermostat
- Halogen chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- Double speed fan
- Timer 0-120 min. + continuous mode
- Adjustable humidity 0-100%

FEATURES

Power		7.500 W
Max temperature		250° C
Weight		85 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)390 mm.
External dimension		(W)880 x (D)935 x (H)710 mm.
Distance between trays		80 mm.
RRP		
Change opening door		

FEATURES

Power		200 W
Gas power		9 kW_7740 Kcal/h
Max temperature		250° C
Weight		93 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)390 mm.
External dimension		(W)880 x (D)935 x (H)900 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Natural gas		Under request
Chimney diameter		ø 100 mm.

ST 604 V7

REF. 710317



4 x 600 x 400

4 x GN 1/1

ST 604 V7 GAS

REF. 710294



4 x 600 x 400

4 x GN 1/1

EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4"
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

FEATURES

Power		7.500 W
Max temperature		270° C
Weight		90 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)390 mm.
External dimension		(W)880 x (D)935 x (H)710 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included

FEATURES

Power		400 W
Gas power		9 kW_7740 Kcal/h
Max temperature		270° C
Weight		98 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)390 mm.
External dimension		(W)880 x (D)935 x (H)900 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included
Natural gas		Under request
Chimney diameter		ø 100 mm.


ST 606

REF. 710319



6 x 600 x 400

6 x GN 1/1



ST 606 GAS

REF. 710320



6 x 600 x 400

6 x GN 1/1

EQUIPMENT

- Cycle end alarm
- Door safety switch
- Safety thermostat
- Halogen chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- Double speed fan
- Timer 0-120 min. + continuous mode
- Adjustable humidity 0-100%

FEATURES

Power		10.500 W
Max temperature		250° C
Weight		97 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)550 mm.
External dimension		(W)880 x (D)935 x (H)870 mm.
Distance between trays		80 mm.
RRP		
Change opening door		

FEATURES

Power		400 W
Gas power		14 kW_12040 Kcal/h
Max temperature		250° C
Weight		108 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)550 mm.
External dimension		(W)880 x (D)935 x (H)1060 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Natural gas		Under request
Chimney diameter		ø 150 mm.


ST 606 V7

REF. 710295



6 x 600 x 400

6 x GN 1/1



ST 606 V7 GAS

REF. 710321



6 x 600 x 400

6 x GN 1/1

EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- 6 Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

FEATURES

Power		10.500 W
Max temperature		270° C
Weight		102 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)550 mm.
External dimension		(W)880 x (D)935 x (H)870 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included

FEATURES

Power		400 W
Gas power		14 kW_12040 Kcal/h
Max temperature		270° C
Weight		113 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)550 mm.
External dimension		(W)880 x (D)935 x (H)1060 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included
Natural gas		Under request
Chimney diameter		ø 150 mm.


ST 610

REF. 710296



10 x 600 x 400

10 x GN 1/1



ST 610 GAS

REF. 710323



10 x 600 x 400

10 x GN 1/1

EQUIPMENT

- Cycle end alarm
- Door safety switch
- Safety thermostat
- Halogen chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- Double speed fan
- Timer 0-120 min. + continuous mode
- Adjustable humidity 0-100%

FEATURES

Power		15.750 W
Max temperature		250° C
Weight		124 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)870 mm.
External dimension		(W)880 x (D)935 x (H)1160 mm.
Distance between trays		80 mm.
RRP		
Change opening door		

FEATURES

Power		600 W
Gas power		18 kW_15840 Kcal/h
Max temperature		250° C
Weight		140 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)870 mm.
External dimension		(W)880 x (D)935 x (H)1350 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Natural gas		Under request
Chimney diameter		ø 150 mm.

ST 610 V7

REF. 710322



10 x 600 x 400

10 x GN 1/1

ST 610 V7 GAS

REF. 710324



10 x 600 x 400

10 x GN 1/1

EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

FEATURES

Power		15.750 W
Max temperature		270° C
Weight		129 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)870 mm.
External dimension		(W)880 x (D)935 x (H)1160 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included

FEATURES

Power		600 W
Gas power		18 kW_15840 Kcal/h
Max temperature		270° C
Weight		145 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)870 mm.
External dimension		(W)880 x (D)935 x (H)1350 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included
Natural gas		Under request
Chimney diameter		ø 150 mm.

ST 721

REF. 710414



7 x GN 2/1

ST 1221

REF. 710420



12 x GN 2/1

EQUIPMENT

- Cycle end alarm
- Door safety switch
- Safety thermostat
- Halogen chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- Double speed fan
- Timer 0-120 min. + continuous mode
- Adjustable humidity 0-100%

FEATURES

Power		18.500 W
Max temperature		250° C
Weight		118 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)744 x (H)550 mm.
External dimension		(W)880 x (D)1227 x (H)870 mm.
Distance between trays		70 mm.
RRP		
Change opening door		

FEATURES

Power		27.750 W
Max temperature		250° C
Weight		162 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)744 x (H)870 mm.
External dimension		(W)880 x (D)1227 x (H)1160 mm.
Distance between trays		70 mm.
RRP		
Change opening door		

ST 721 V7

REF. 710418



7 x GN 2/1

ST 1221 V7

REF. 710419



12 x GN 2/1

EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

FEATURES

Power		18.500 W
Max temperature		270° C
Weight		124 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)744 x (H)550 mm.
External dimension		(W)880 x (D)1227 x (H)870 mm.
Distance between trays		70 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included

FEATURES

Power		27.750 W
Max temperature		270° C
Weight		170 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)744 x (H)870 mm.
External dimension		(W)880 x (D)1227 x (H)1160 mm.
Distance between trays		70 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included


NEW

ST 616 V7

REF. 710325



16 x 600 x 400



EQUIPMENT


- Climate Control-adjustable humidity
- Fan Control-Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4
- Folding inner glass for cleaning
- Reversing gear
- USB port
- External Core Probe connection
- HACCP
- Multi Level

FEATURES

Capacity		16 x 600 x 400 - 16 x GN 1/1
Power		28.750 W
Max temperature		270° C
Weight		206 Kg.
Voltage		400 V - 50/60 Hz
Connection		Three phase 3F + N + T
Cooking chamber dimension		(W)700 x (D)500 x (H)1470 mm.
External dimension		(W)880 x (D)960 x (H)1865 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included

ST 616 V7 GAS

REF. 710326




EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection $\frac{3}{4}$
- Folding inner glass for cleaning
- Reversing gear
- USB port
- External Core Probe connection
- HACCP
- Multi Level

FEATURES

Capacity		16 x 600 x 400 - 16 x GN 1/1
Power		1.000 W
Gas power		33 kW_28380 Kcal/h
Max temperature		270° C
Weight		252 Kg.
Voltage		230 V - 50/60 Hz
Connection		SINGLE PHASE
Cooking chamber dimension		(W)700 x (D)500 x (H)1470 mm.
External dimension		(W)880 x (D)1000 x (H)2055 mm.
Distance between trays		80 mm.
RRP		
Change opening door		
Automatic washing system		Included
Core Prober		Included
Natural gas		Under request
Chimney diameter		ø 180 mm.




EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- 6 Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

FEATURES	ST-616-V7-T Ref. 710297	ST-211-V7 Ref. 710329	ST-211-V7-T Ref. 710330	ST-221-V7 Ref. 710333	ST-221-V7-T Ref. 710334
Capacity	16 x 600 x 400	20 x Gn 1/1	20 x Gn 1/1	20 x Gn 2/1 40 x Gn 1/1	20 x Gn 2/1 40 x Gn 1/1
Power	28.750 W	28.750 W	28.750 W	46.250 W	46.250 W
Gas power	-	-	-	-	-
Max temperature	270° C	270° C	270° C	270° C	270° C
Weight	198 Kg.	206 Kg.	206 Kg.	244 Kg.	232 Kg.
Voltage	400 V - 50/60 Hz	400 V - 50/60 Hz	400 V - 50/60 Hz	400 V - 50/60 Hz	400 V - 50/60 Hz
Connection	Three phase 3F + N + T	Three phase 3F + N + T	Three phase 3F + N + T	Three phase 3F + N + T	Three phase 3F + N + T
Cooking chamber dimension	(W)700x(D)500x(H)1470 mm.	(W)700x(D)500x(H)1470 mm.	(W)700x(D)500x(H)1470 mm.	(W)700x(D)740x(H)1470 mm.	(W)700x(D)740x(H)1470 mm.
External dimension	(W)880x(D)960x(H)1850 mm.	(W)880x(D)960x(H)1865 mm.	(W)880x(D)960x(H)1865 mm.	(W)880x(D)1200x(H)1865 mm.	(W)880x(D)1200x(H)1865 mm.
Distance between trays	80 mm.	65 mm.	65 mm.	65 mm.	65 mm.
RRP					
Change opening door					
Automatic washing system	Included	Included	Included	Included	Included
Core Prober	Included	Included	Included	Included	Included
Natural gas	-	-	-	-	-
Chimney diameter	-	-	-	-	-
Trolley	✓	✗	✓	✗	✓

STANDS PORTATRAYS FIJOS

TROLLEY PORTATRAYS EXTRAIBLE INCLUIDO



EQUIPMENT

- Climate Control-adjustable humidity
- Fan Control-Fan Control-adjustable speed
- Steam Control-adjustable chimney
- Delta T
- External Core Probe connection
- 6 Cooking phases
- Regeneration / Maintenance
- Recipe book
- Favorites
- Cool Down / Preheat
- Cycle end alarm
- Door sensor
- Safety thermostat
- LED chamber light
- Water connection 3/4
- Folding inner glass for cleaning
- Reversing gear
- USB port
- HACCP
- Multi Level

	🔥 ST-616-V7-GAS-T	🔥 ST-211-V7-GAS	🔥 ST-211-V7-GAS-T	🔥 ST-221-V7-GAS	🔥 ST-221-V7-GAS-T
	Ref. 710303	Ref. 710331	Ref. 710332	Ref. 710335	Ref. 710336
Capacity	16 x 600 x 400	20 x Gn 1/1	20 x Gn 1/1	20 x Gn 2/1 40 x Gn 1/1	20 x Gn 2/1 40 x Gn 1/1
Power	1.000 W	1.000 W	1.000 W	1.000 W	1.000 W
Gas power	33 Kw_28380 Kcal/h	33 Kw_28380 Kcal/h	33 Kw_28380 Kcal/h	50 Kw_43000 Kcal/h	50 Kw_43000 Kcal/h
Max temperature	270° C	270° C	270° C	270° C	270° C
Weight	244 Kg.	252 Kg.	244 Kg.	300 Kg.	288 Kg.
Voltage	230 V - 50/60 Hz	230 V - 50/60 Hz	230 V - 50/60 Hz	230 V - 50/60 Hz	230 V - 50/60 Hz
Connection	Shuko SINGLE PHASE	Shuko SINGLE PHASE	Shuko SINGLE PHASE	Shuko SINGLE PHASE	Shuko SINGLE PHASE
Cooking chamber dimension	(W)700x(D)500x(H)1470 mm.	(W)700x(D)500x(H)1470 mm.	(W)700x(D)500x(H)1470 mm.	(W)700x(D)740x(H)1470 mm.	(W)700x(D)740x(H)1470 mm.
External dimension	(W)880x(D)1000x(H)2055 mm.	(W)880x(D)1000x(H)2055 mm.	(W)880x(D)1000x(H)2055 mm.	(W)880x(D)1240x(H)2055mm.	(W)880x(D)1240x(H)2055mm.
Distance between trays	80 mm.	65 mm.	65 mm.	65 mm.	65 mm.

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89

Иваново (4932)77-34-06
Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47 Казахстан (772)734-952-31 Таджикистан (992)427-82-92-69

<http://fmind.nt-rt.ru> || fdm@nt-rt.ru